

Stansolv AK-22 381

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (inches)** 14
- **Thickness (inches)** 0.033 (Med. Wt.)
- **Wrist** Scalloped cuff
- **Colour/Color** Green
- **Interior finish** Textile support Mapa Technology
- **Exterior finish** Embossed texture
- **Size / EAN** 6 7 8 9 10 11
- **Packaging** 12 pairs/bag - 72 pairs/carton
- **Complementary information** Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

CE 0334



X1XXXX



AJKL



3121

Legends



**MECHANICAL
HAZARDS
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Abrasion resistance
 └─ Blade cut resistance
 └─ Tear resistance
 └─ Puncture resistance



**LOW CHEMICAL
PROTECTION
EN 374**



**MICRO-ORGANISMS
EN 374**



**RADIOACTIVE
CONTAMINATION
EN 421**



**HEAT
AND FIRE
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Burning behaviour
 └─ Contact heat resistance
 └─ Convective heat resistance
 └─ Radiant heat resistant
 └─ Resistance to small drops of molten metal
 └─ Resistance to large quantities of molten metal



**SPECIFIC CHEMICAL
PROTECTION
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofuran
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Convective cold resistance
 └─ Contact cold resistance
 └─ Water permeability

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL
www.mapa-pro.com

DESCRIPTION AND GENERAL PROPERTIES

- Extremely supple, due to the unique Mapa multi-layer process
- Embossed texture for better grip of wet objects
- Added comfort and thermal insulation, due to the cotton-knit lining

MAIN FIELDS OF USE

Automotive/mechanical industry

- [Surface treatment](#)
- Part degreasing
- Automotive assembly

Other industries

- [Machine maintenance](#)
- Laboratory tests

Chemical industry

- [Handling drums of chemical products](#)
- Chemical product blending
- Manipulating valves

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at the workplace may differ from the «CE»-type tests.
- It is not recommended for persons sensitized to dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service • MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their packaging protected from light and humidity.

Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with paints, pigments and inks: wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (diluent, etc...): rub over with a dry cloth
- in use with acids or alkalies: thoroughly rinse the gloves under running water, and rub over with a dry cloth.

Caution : improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

PROFESSIONAL

www.mapa-pro.com

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament