

# Product Specifications

Item # 1555W



## Magid® CutMaster® 1555W Thermal Leather Drivers Glove – Cut Level A6

For jobs that require protection from sharp materials in cold conditions, the 1555W Thermal Leather Drivers Glove combines durable cow grain leather with Hyperon™ blended Insulcore™ Thermal Lining to deliver superior dexterity, durability, and ANSI level A6 cut protection.

### PRODUCT DESCRIPTION

<b>Product Classification</b>	Leather Drivers Gloves – Cut Resistant and Cold Weather
<b>Construction/Design</b>	Gunn cut pattern, keystone thumb, shirred elastic at wrist
<b>Composition</b>	Cow Grain leather shell; HPPE blended acrylic fleece liner
<b>Color(s)</b>	White
<b>Size(s)</b>	S-XXXL
<b>Unit of Measure</b>	Pair
<b>Packaging</b>	1 dozen pairs per inner pack, 6 inner packs per case (6 dozen pairs per case)

### FEATURES & BENEFITS

- Durable cow grain leather shell provides dexterity and abrasion resistance
- Hyperon™ blended Insulcore™ Thermal Lining defends against cold temperatures and provides dependable cut protection
- Gunn cut pattern increases comfort and dexterity
- Shirred elastic on back improves fit
- ANSI Level A6 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 4 Puncture Resistance

### APPLICATIONS

Outdoor metal handling, transportation, heavy construction and agriculture.

### AVAILABLE STYLES

Size	S	M	L	XL	XXL	XXXL
Item #	1555WS	1555WM	1555WL	1555WXL	1555WXXL	1555WXXXL

## FUNCTIONAL PERFORMANCE

### US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A6
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4

### US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistance	-	4

## SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

**Critical Defects**

Holes/tears

**Major Defects**

Dimensional or weight nonconformance, discoloration, other fabric defects

## LAUNDERING GUIDELINES

For best results, leather gloves should be dry-cleaned only

<b>Originator</b>	Jennifer Walrich	<b>Date</b>	08/09/2016	
<b>Revised By</b>		<b>Date</b>		<b>Revision #</b>

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD