

# Product Specifications

Item #23075BCM

**MAGID**

Safety at work™

**Magid® Double Layer Nylon Soft Black Cane Mesh  
Sleeve – Cut Level 3**

## PRODUCT DESCRIPTION

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| <b>Product Classification</b> | Special Purpose Sleeves – Cut Resistant              |
| <b>Construction/Design</b>    | 12 – 15" x 7.75" double layer Nylon cane mesh sleeve |
| <b>Composition</b>            | 100% soft black nylon                                |
| <b>Color(s)</b>               | Black and yellow                                     |
| <b>Size(s)</b>                | 12-15" x 9"                                          |
| <b>Unit of Measure</b>        | Pair                                                 |
| <b>Packaging</b>              | 12 pairs per inner pack, 96 pairs per case           |

## FEATURES & BENEFITS

- Heavyweight nylon material is soft and cost effective
- Double layer nylon cane mesh construction for excellent cut and abrasion resistance
- Velcro closure for easy removal and size adjustment
- Can be laundered multiple times

## APPLICATIONS

Automotive, appliance industry, metal stamping, metal fabrication and assembly.

## AVAILABLE STYLES

| Size          | S           | M           | L           | XL          |
|---------------|-------------|-------------|-------------|-------------|
| <b>Item #</b> | 23075BCMS   | 23075BCMM   | 23075BCML   | 23075BCMXL  |
| <b>Size</b>   | 12" x 7.75" | 13" x 7.75" | 14" x 7.75" | 15" x 7.75" |

**MAGID**

Safety at work™

| FUNCTIONAL PERFORMANCE                                                                                                                                                                                          |                                                                           |            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|------------|
| US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria                                                                                                               |                                                                           |            |
| Test Method                                                                                                                                                                                                     | Clause                                                                    | ANSI Level |
| Cut Resistance                                                                                                                                                                                                  | -                                                                         | 3          |
| SERVICE LIFE                                                                                                                                                                                                    |                                                                           |            |
| The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted. |                                                                           |            |
| Critical Defects                                                                                                                                                                                                | Holes/tears                                                               |            |
| Major Defects                                                                                                                                                                                                   | Dimensional or weight nonconformance, discoloration, other fabric defects |            |
| LAUNDERING GUIDELINES                                                                                                                                                                                           |                                                                           |            |
| It is recommended that the sleeves be machine washed. The water temperature cannot exceed 40°C/104°F. Do not use bleach. The sleeves can be air dried or tumbled dry on low temp.                               |                                                                           |            |

|            |                  |      |            |  |
|------------|------------------|------|------------|--|
| Originator | Jennifer Walrich | Date | 07/08/2016 |  |
| Revised By |                  |      |            |  |

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

