

Product Specifications

Item # AXFR143LP



MAGID

**Magid® 14" FR Aramax® Sleeve with Thumb Slot –
ANSI Cut Level 3**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Sleeve – Cut Resistant
Construction/Design	Tubular knit with thumb slot; 9.5" leather patch affixed to sleeve with six bar tacks and glue; ambidextrous
Composition	FR Aramax® yarn; elastic overedges on thumb slot, finger slot, and bicep; leather patch
Color(s)	Dark yellow/green sleeve; yellow overedges; white patch
Size(s)	14" long, 3" wide
Unit of Measure	Each
Packaging	24 per inner pack, 240 per case; minimum order quantity of 12 each

FEATURES & BENEFITS	
• Aramax® FR yarn, single-ply, seamless machine knit sleeves with flame- resistant properties are ideal for stamping, assembly, and glass and metal handling when flames or spark hazards are present • Leather patch increases abrasion resistance for added durability and extended wear • Single-ply construction provides the protection of a two-ply sleeve in the comfort-enhancing construction of a single-ply • Engineered to breathe easily and wick away moisture from the skin • Dark coloration hides dirt and grime, extending the life of the sleeve • Sleeves are machine washable and can be reused without compromising performance • Elastic at bicep keeps the sleeve secure on the wearer's arm • ANSI Cut Level 3 protection	

APPLICATIONS	
Metal stamping, metal fabrication, automotive manufacturing, household appliance assembly, aerospace manufacturing, paper production, glass fabrication as well as any heavy-duty application where laceration, abrasion, flame or spark hazards may be present.	

AVAILABLE STYLES	
Size	14"
Item #	AXFR143LP

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistance	-	3
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
It is recommended that the sleeves be machine washed. The water temperature cannot exceed 40°C/104°F. Do not use bleach. The sleeves can be air dried or tumbled dry low temp.		

Originator	Dana Cornish	Date	4/29/2021	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

