

Product Specifications

Item # AXFR22BST



Magid® CutMaster® Aramax® XT Fire Resistant Blousy Sleeve – Cut Level 4

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Sleeve – Cut Resistant
Construction/Design	Seamless tubular machine knit
Composition	100% Aramax® XT FR
Color(s)	Yellow/green
Size(s)	22"
Unit of Measure	Each
Packaging	24 per inner pack, 144 per case

FEATURES & BENEFITS	
• Yellow/green, lightweight, 100% Aramax® XT FR Yarn, single-ply, seamless machine knit sleeves with flame- resistant properties are ideal for stamping, assembly, and glass and metal handling when flames or spark hazards are present • Aramax™ XT FR sleeves offer up to two times greater cut protection and up to two-and-a-half times greater abrasion resistance than gloves of a similar weight made from 100% para-aramid • Single-ply construction provides the protection of a two-ply sleeve in the comfort-enhancing construction of a single-ply • Specially engineered to wick away moisture and to allow more air transfer, Aramax™ XT FR Sleeves stay cooler and breathe easier to provide superior comfort • Dark yellow/green coloration hides dirt reducing disposal and extending wear • Washable fabric can be used over and over without compromising performance • 4" width and 22" lengths with thumb slot • ANSI CUT Level 4	

APPLICATIONS		
Metal stamping, metal fabrication, automotive manufacturing, household appliance assembly, aerospace manufacturing, paper production, glass fabrication as well as any heavy-duty application where laceration, abrasion, flame or spark hazards may be present.		
AVAILABLE STYLES		
Size	22"	
With Thumb Slot	AXFR22BST	
FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
Cut Resistance	-	4
ASTM D6413 / D6413M - 15 Vertical Test Method for Flame Resistance of Textiles		
Test Method	Pass/Fail?	
Flame Resistance (Vertical Test)	Pass	
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
It is recommended that the sleeves be machine washed. The water temperature cannot exceed 40°C/104°F. Do not use bleach. The sleeves can be air dried or tumbled dry low temp.		

Originator	Jennifer Walrich		4/7/2016	
Revised By	Scott Daigle		1/16/2018	

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.