

Product Specifications

Item # AXTFR223G, AXTFR224G



M-GARD®

**Magid® M-Gard® Aramax® XT Flame Resistant Sleeve
– Cut Level 4**

For stamping, assembly, and glass or metal handling applications when flames or spark hazards are present, the Magid® CutMaster® AXTFR Aramax XT Flame Resistant Knit Sleeve offers lightweight, single-ply ANSI level 4 cut protection plus flame resistance.

PRODUCT DESCRIPTION

Product Classification	Special Purpose Sleeve – Cut Resistant
Construction/Design	Tubular machine knit, gusset, elastic closure at bicep
Composition	100% Aramax® XT FR
Color(s)	Yellow/green
Size(s)	22" long and 3" wide or 4" wide
Unit of Measure	Each
Packaging	24 per inner pack, 240 per case

FEATURES & BENEFITS

- Magid's exclusive Aramax XT FR Yarn delivers unrivaled cut and abrasion resistance, comfort and durability with flame resistance
- Protection of a two-ply sleeve in the comfort-enhancing construction of a single-ply
- Moisture-wicking material allows for air flow to keeps the wearer cool and comfortable
- Gusset and elastic at the bicep for added fit and comfort
- Washable fabric can be used over and over without compromising performance
- ANSI Level 4 Cut Resistance
- Made in the U.S.A.

APPLICATIONS

Metal stamping, metal fabrication, automotive manufacturing, household appliance assembly, aerospace manufacturing, paper production, glass fabrication as well as any heavy-duty application where laceration, abrasion, flame or spark hazards may be present.

AVAILABLE STYLES

Width	3"	4"
Item #	AXTFR223G	AXTFR224G

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
Cut Resistance	-	4
ASTM D6413 / D6413M - 15 Vertical Test Method for Flame Resistance of Textiles		
Test Method	Pass/Fail?	
Flame Resistance (Vertical Test)	Pass	
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
It is recommended that the sleeves be machine washed. The water temperature cannot exceed 40°C/104°F. Do not use bleach. The sleeves can be air dried or tumbled dry low temp.		

Originator	Jennifer Walrich	Date	10/24/18	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

