

Product Specifications

Style #DXG22



D-ROC®

Magid® D-ROC® DX™ Technology DXG22 18-gauge Polyurethane Palm Coated Coreless Work Glove – Cut Level A3

The DXG22 work gloves feature DX™ Technology – an engineered yarn that uses strength enhancing micro particles so steel and fiberglass are no longer needed to achieve higher levels of cut protection. The result is an extremely comfortable, cut-resistant yarn that is 20% lighter in weight, non-irritating and cool to the touch.

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit
Composition	DX™ Technology shell; polyurethane palm coating
Color(s)	Hi-viz orange shell; grey palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
• New DX™ Technology uses non-irritating strength enhancing micro particles to achieve higher levels of cut protection without the discomfort that fiberglass or steel can cause • DX Technology engineered yarn delivers extreme comfort that is 20% lighter than a traditional HPPE shell of the same cut level • DX Technology feels cool to the touch which keeps the wearer cool and comfortable while working • Polyurethane palm coating maintains dexterity while delivering excellent grip • High-visibility color enhances worker protection and ensures worker compliance • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • 360° ANSI Level A3 Cut Resistance, ANSI Level 4 Abrasion Resistance, and ANSI Level 3 Puncture Resistance	

APPLICATIONS	
Assembly, Appliance Manufacturing, Automotive, Construction, Maintenance, Material Handling, and Metal Handling as well as any application where laceration or abrasion hazards and oil and lubricants may be present.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	DXG225	DXG226	DXG227	DXG228	DXG229	DXG2210	DXG2211	DXG2212
FUNCTIONAL PERFORMANCE								
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria								
Test Method					Clause	ANSI Level		
ASTM F2992-15 Cut Resistance					-	A3		
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)					-	4		
EN 388:2003 Puncture Resistance					6.4	3		
SERVICE LIFE								
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.								
Critical Defects		Holes/tears						
Major Defects		Dimensional or weight nonconformance, discoloration, other fabric defects						
LAUNDERING GUIDELINES								
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.								
GENERAL INFORMATION								
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.								

Originator	Scott Daigle	Date	12/5/2017	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.