

Product Specifications

Style #DXG42



D-ROC®

Magid® D-ROC® DX Technology® DXG42 13-Gauge
Polyurethane Palm Coated Work Glove – Cut Level A4

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	DX Technology® shell; polyurethane palm coating
Color(s)	Hi-viz orange shell; grey palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)
FEATURES & BENEFITS	
- DX Technology® uses non-irritating strength enhancing micro particles to achieve higher levels of cut protection without the discomfort that fiberglass or steel can cause - DX Technology engineered yarn delivers extreme comfort that is 20% lighter than a traditional HPPE of the same cut level - DX Technology feels cool to the touch which keeps the wearer cool and comfortable while working - Polyurethane palm coating maintains dexterity while delivering excellent grip - High-visibility color enhances worker protection and compliance - Shield graphic is color-coded by cut level to easily identify cut protection from a distance - Color-coded overcast acts as a visual aid for sizing and reduces fraying - Machine washable for longer service life - PPG and NEAT Tested - ANSI Level A4 Cut Resistance, ANSI Level 6 Abrasion Resistance, and ANSI Level 4 Puncture Resistance	

APPLICATIONS

Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling, Metal Stamping, and Paper Production as well as any application where laceration or abrasion hazards and oil and lubricants may be present.

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	DXG425	DXG426	DXG427	DXG428	DXG429	DXG4210	DXG4211	DXG4212

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A4
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	6
ANSI/ISEA: 105-2011 Puncture Resistance	6.4	4

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	12/5/2017	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.