

Product Specifications

Style #DXG49



D-ROC®

Magid® D-ROC® DX Technology® 13-gauge TriTek Palm™
Three-Quarter Coated Work Glove – Cut Level A4

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	DX Technology® shell; TriTek Palm™ 3/4 coating
Color(s)	Hi-viz orange shell; black coating
Size(s)	6 – 12
Cuff/Finish	Color-coded elasticized overcast: grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case
FEATURES & BENEFITS	
• TriTek Palm™ three-quarter coating strengthens grip and minimizes saturation in heavy liquid and oil applications • Resilient TriTek coating provides over 2X the abrasion resistance of other coatings for unbeatable durability while maintaining extreme dexterity • DX Technology® uses non-irritating strength enhancing micro particles to achieve higher levels of cut protection without the discomfort that fiberglass or steel can cause • 13-Gauge DX Technology engineered yarn delivers extreme comfort that is 20% lighter than a traditional HPPE of the same cut level • DX Technology feels cool to the touch which keeps the wearer cool and comfortable while working • Reinforced thumb saddle enhances durability at a critical wear point • High-visibility shell color enhances worker protection and ensures worker compliance • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A4 Cut Resistance, ANSI Level 6 Abrasion Resistance, and ANSI Level 3 Puncture Resistance	

APPLICATIONS							
Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling , Metal Stamping, Paper Production							
AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Item Number	DXG496	DXG497	DXG498	DXG499	DXG4910	DXG4911	DXG4912
FUNCTIONAL PERFORMANCE							
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria							
Test Method					Clause	ANSI Level	
ASTM F2992-15 Cut Resistance					-	A4	
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)					-	6	
ANSI/ISEA: 105-2011 Puncture Resistance (other than hypodermic needle)					6.4	3	
ASTM F1060-18 Standard Test Method for Evaluation of Conductive and Compressive Heat Resistance (CCHR)							
Test Method					Level	Result	
ASTM F1060-18 Conductive and Compressive Heat Resistance					1	80°C (176°F)	
SERVICE LIFE							
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.							
Critical Defects	Holes/tears						
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects						
LAUNDERING GUIDELINES							
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.							
GENERAL INFORMATION							
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.							

Originator	Scott Daigle	Date	9/2/2020	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.