

Product Specifications

Style #DXPG52



D-ROC®

Magid® D-ROC® DX+ Technology® DXPG52 15-gauge
Polyurethane Palm Coated Coreless Work Glove – Cut
Level A5

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	15-gauge, seamless machine knit
Composition	DX+ Technology® shell; polyurethane palm coating
Color(s)	Orange shell; grey palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS

- Coreless DX+ Technology® uses non-irritating strength enhancing micro-particles to achieve higher levels of cut protection without the discomfort that fiberglass or steel can cause
- Premium 15-gauge DX+ Technology® engineered yarn delivers extreme comfort that is 30% lighter than a traditional HPPE of the same cut level
- DX+ Technology® feels cool to the touch which keeps the wearer cool and comfortable while working
- Polyurethane palm coating maintains dexterity while delivering excellent grip
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- Machine washable for longer service life
- PPG Tested
- ANSI Level A5 Cut Resistance, ANSI Level 4 Abrasion Resistance, and ANSI Level 4 Puncture Resistance

APPLICATIONS

Assembly, Appliance Manufacturing, Automotive, Construction, Maintenance, Material Handling, and Metal Handling as well as any application where laceration or abrasion hazards and oil and lubricants may be present.

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	DXPG525	DXPG526	DXPG527	DXPG528	DXPG529	DXPG5210	DXPG5211	DXPG5212

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

Originator	Dana Cornish	Date	4/4/2022	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD