

# Product Specifications

Style #DXPG59Q



## D-ROC®

Magid® D-ROC® DX+ Technology® DXPG59Q 18-Gauge Double-Dipped Foam Nitrile 3/4 Coated Coreless Work Glove – Cut Level A5

### PRODUCT DESCRIPTION

<b>Product Classification</b>	Special Purpose Work Glove – Cut Resistant, Coated
<b>Construction/Design</b>	18-gauge, seamless machine knit
<b>Composition</b>	DX+ Technology® shell; foam nitrile 3/4 coating, nitrile undercoat
<b>Color(s)</b>	Orange shell; black palm coating; red 3/4 undercoat
<b>Size(s)</b>	7 – 12
<b>Cuff/Finish</b>	Color-coded elasticized overcast: blue (7), green (8), red (9), black (10), orange (11), white (12)
<b>Unit of Measure</b>	Pair
<b>Packaging</b>	12 pairs per inner pack, 144 pairs per case, 12 pair minimum order increment

### FEATURES & BENEFITS

- Coreless DX+ Technology® uses non-irritating strength enhancing micro-particles to achieve higher levels of cut protection without the discomfort that fiberglass or steel can cause
- Premium 18-gauge DX+ Technology® engineered yarn delivers extreme comfort that is 30% lighter than a traditional HPPE of the same cut level
- DX+ Technology® feels cool to the touch which keeps the wearer cool and comfortable while working
- Foam nitrile palm coating channels oil away for superb grip in light oil applications
- ¾ Nitrile undercoat protects against liquids, oils, and solvents
- Shield graphic is color-coded by cut level to easily identify cut protection from a distance
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- Machine washable for longer service life
- ANSI Level A5 Cut Resistance, ANSI Level 5 Abrasion Resistance, and ANSI Level 4 Puncture Resistance

### APPLICATIONS

Assembly, Appliance Manufacturing, Automotive, Construction, Maintenance, Material Handling, and Metal Handling as well as any application where laceration or abrasion hazards and oil and lubricants may be present.

### AVAILABLE STYLES

Size	7	8	9	10	11	12
Item Number	DXPG59Q7	DXPG59Q8	DXPG59Q9	DXPG59Q10	DXPG59Q11	DXPG59Q12

### FUNCTIONAL PERFORMANCE

#### US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	5
EN 388:2003 Puncture Resistance	6.4	4

### SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

<b>Critical Defects</b>	Holes/tears
<b>Major Defects</b>	Dimensional or weight nonconformance, discoloration, other fabric defects

### LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

<b>Originator</b>	Scott Daigle	<b>Date</b>	10/17/2022	
<b>Revised By</b>	Brittany Cohen	<b>Date</b>	02/06/2023	<b>Revision #</b> 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

WD

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.