

16" Hazmax Steel Toe W/Ladder Shank (8701200)

The boot that continues to set the standard for biological hazards and waste protection



General

Segment	Industry
Material boot shaft	Hazmax®
Material outsole	Hazmax®
Color shaft	Green
Color outsole	Bright Yellow
Insole type	Standard insole

Certification

Safety standard USA	NFPA 1991 & ASTM F2418-11 M I/75 C/75 PR EH
Safety standard Canada	CSA Z195-14 PR Omega

Protection & Comfort

Toe cap	Steel
Midsole	Steel
Oil resistant outsole	Yes
Energy absorbing	Yes
Electrical insulation	Insulating
Fuel oil resistant	Yes

Sizing

Size range US	06-17
---------------	-------

Logistics

Country of origin	United States of America
Intrastat code	64011000

USP Outsole

Steel toe, steel midsole and steel shank Ultragrip® Sipe outsole provides superior, slip resistance and protection

USP Shaft

Specially formulated PVC allow protects you from some of the worst chemicals arounds while exceeding CSA standards for Di-Electric footwear

USP Safety

Certified by S.E.I. to meet the requirements of NFPA 1990-2022 (NFPA 1991) Standard on Vapor-protective ensembles for Hazardous materials emergencies, Flash Fire certified

SKU	Size EUR	Size US	Size UK	GTIN	Prs/Outer pack	Outer pack length (mm)	Outer pack width (mm)	Outer pack height (mm)	Prs/Pallet	Pallet height (mm)
8701200.06	06			791079135877	6	542.925	469.9	314.325	132	1880.7875
8701200.07	07			791079135884	6	542.925	469.9	314.325	132	1880.7875
8701200.08	08			791079135891	6	542.925	469.9	314.325	132	1880.7875
8701200.09	09			791079135907	6	542.925	469.9	314.325	132	1880.7875
8701200.10	10			791079135914	6	542.925	469.9	314.325	132	1880.7875
8701200.11	11			791079135921	6	542.925	469.9	314.325	132	1880.7875
8701200.12	12			791079135938	6	542.925	469.9	314.325	132	1880.7875
8701200.13	13			791079135945	6	560	469.9	320	90	1902
8701200.14	14			791079135952	6	560	469.9	320	90	1902
8701200.15	15			791079135969	6	560	469.9	320	90	1902
8701200.17	17			791079153994	6	560	469.9	320	90	1902