

# Product Specifications

Item #GP102



Magid® ROC® GP102 Sustainable Lightweight Foam  
Nitrile Palm Coated Work Glove

## PRODUCT DESCRIPTION

<b>Product Classification</b>	General Purpose Work Glove – Coated
<b>Construction/Design</b>	15-gauge, seamless machine knit
<b>Composition</b>	Recycled polyester and spandex blend shell with foam nitrile palm coating
<b>Color(s)</b>	Grey shell; black palm coating
<b>Size(s)</b>	5 – 12
<b>Cuff/Finish</b>	Color-coded elasticized overcast: light blue (5), navy blue (6), purple (7), green (8), brown (9), yellow (10), grey (11), white (12)
<b>Unit of Measure</b>	Dozen
<b>Packaging</b>	12 inner packs per case (144 pairs per case)

## FEATURES & BENEFITS

- Soft, flexible, and sustainably manufactured foam nitrile coating ensures great grip of small parts even in wet/oily conditions
- 90% recycled polyester and 10% spandex blend shell adds stretch and breathability
- Dark color hides dirt and grime to extend wear
- Silicone-free, low-lint construction minimizes product contamination
- Color-coded overcast for easy sorting and dispensing
- Rubber band edge reduces fraying
- Industry-leading pricing makes for an excellent value
- Packaged in 100% recycled materials
- Meets Global Recycled Standard V4.0; Content Claim Standard V3.1; Textile Exchange Standard Claims Policy V1.2
- ANSI Level 4 Abrasion Resistance

## APPLICATIONS

Assembly, shipping and receiving, material handling and general maintenance.

**AVAILABLE STYLES**

<b>Size</b>	<b>5</b>	<b>6</b>	<b>7</b>	<b>8</b>	<b>9</b>	<b>10</b>	<b>11</b>	<b>12</b>
<b>Part Number</b>	GP1025	GP1026	GP1027	GP1028	GP1029	GP10210	GP10211	GP10212

**FUNCTIONAL PERFORMANCE**

**US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria**

<b>Test Method</b>	<b>Clause</b>	<b>ANSI Level</b>
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4

**SERVICE LIFE**

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

<b>Critical Defects</b>	Holes/tears
<b>Major Defects</b>	Dimensional or weight nonconformance, discoloration, other fabric defects

**LAUNDERING GUIDELINES**

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water, and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

<b>Originator</b>	Kim Schultz	<b>Date</b>	04/25/2023	
<b>Revised By</b>	Kim Schultz	<b>Date</b>	02/06/2024	<b>Revision #</b> 4

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD