

Product Specifications

Item #GP110



ROC®

Magid® ROC® GP110 Lightweight Foam Nitrile Coated Work Glove

PRODUCT DESCRIPTION	
Product Classification	General Purpose Work Glove – Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Nylon blended shell with full foam nitrile coating
Color(s)	Grey shell; black coating
Size(s)	6 – 11
Cuff/Finish	Color-coded elasticized overcast: white (6), green (7), brown (8), yellow (9), grey (10), black (11)
Unit of Measure	Dozen
Packaging	12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
• Soft, flexible foam nitrile coating ensures great grip of small parts even in wet/oily conditions • Full foam nitrile coating extends protection to the back of the hand • High-density nylon and spandex shell adds stretch and breathability • Dark color hides dirt and grime to extend wear • Color-coded overcast reduces fraying and acts as a visual aid for sizing • Industry-leading pricing makes for an excellent value • ANSI Cut Level 1 Cut Resistance and ANSI Level 4 Abrasion Resistance	

APPLICATIONS	
Assembly, shipping and receiving, material handling and general maintenance.	

AVAILABLE STYLES						
Size	6	7	8	9	10	11
Part Number	GP1106	GP1107	GP1108	GP1109	GP11010	GP11011

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	1
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	2

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
-------------------------	-------------

Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects
----------------------	---

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water, and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Lisa Bucki	Date	07/19/2012	
Revised By	Kim Schultz	Date	11/09/2023	Revision # 6

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.