

Product Specifications

Item #GP148



ROC[®]

Magid[®] ROC[®] GP148 Lightweight TriTek Palm[®]
Coated General Purpose Work Glove

PRODUCT DESCRIPTION	
Product Classification	General Purpose Work Glove – Coated
Construction/Design	15-gauge, seamless machine knit
Composition	Nylon/Spandex blend shell; TriTek Palm [®] coating
Color(s)	Navy blue shell; grey palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Dozen (minimum order: 12 dozen)
Packaging	12 dozen pairs per inner pack, 144 dozen per case

FEATURES & BENEFITS	
<ul style="list-style-type: none">• 15-gauge nylon and spandex shell is form-fitting and breathable for a bare-hands feel• Flexible dual-layer TriTek Palm[®] coating strengthens grip and minimizes saturation in heavy liquid and oil applications• Resilient TriTek Palm coating provides over 2X the abrasion resistance of other coatings for unbeatable durability while maintaining extreme dexterity• Color-coded overcast acts as a visual aid for sizing and reduces fraying• Machine washable for longer service life• ANSI Level 4 Abrasion Resistance	

APPLICATIONS	
Shipping and receiving, assembly, material handling, and general maintenance	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Part Number	GP1485	GP1486	GP1487	GP1488	GP1489	GP14810	GP14811	GP14812

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Scott Daigle	Date	12/9/2019	
Revised By	Dana Cornish	Date	4/25/2022	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD