

Product Specifications

Item #GP180



Magid® ROC® Ultra-Lightweight Polyurethane Palm Coated Work Glove

For jobs that involve precision handling of small and fine parts, the GP180 ultra-lightweight polyurethane palm coated work glove delivers the highest degree of dexterity and tactile sensitivity.

PRODUCT DESCRIPTION								
Product Classification	General Purpose Coated Work Glove							
Construction/Design	18-gauge, seamless machine knit							
Composition	Polyester shell; polyurethane palm coating							
Color(s)	Black shell; black palm coating							
Size(s)	5 – 12							
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)							
Unit of Measure	Dozen							
Packaging	12 pairs per inner pack, 12 inner packs per case							
FEATURES & BENEFITS								
• ANSI Level 0 Cut Resistance and ANSI Level 3 Abrasion Resistance • Ultra-lightweight, form-fitting 18-gauge construction delivers exceptional comfort and the dexterity of bare hands • All black color hides dirt and extends worker wear time • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life								
APPLICATIONS								
Assembly, maintenance, material handling and shipping & receiving. Especially good for jobs that require handling small parts.								
AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GP1805	GP1806	GP1807	GP1808	GP1809	GP18010	GP18011	GP18012

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	0
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	3
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.		

Originator	Sarah Anderson	Date	05/02/2015	
Revised By		Date		Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

