

Product Specifications

Item #GP600W



D-ROC®
by Magid

Magid® ROC® Thermal Double-Dip Coated Work Gloves – Cut Level A2

For jobs that require handling sharp or abrasive materials in cold conditions, the GP600W Insulcore™ Thermal Lined work glove provides warmth and superior grip while concealing dirt and grime.

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	7-gauge, insulated seamless machine knit shell
Composition	100% polyester with acrylic fleece liner; NitriX® Grip Technology double-dip palm
Color(s)	Black shell; black palm coating
Size(s)	7 – 11
Cuff/Finish	Color-coded elasticized overcast: light blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	PR
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS

- Insulcore™ Thermal Lining defends against cold temperatures
- 100% polyester with acrylic fleece liner shell delivers breathability, comfort, and 360° cut protection
- NitriX® Grip Technology double dip palm coating delivers a superior grip and longer wear life
- Black color hides dirt extends worker wear time
- ANSI Level A2 Cut Resistance and ANSI Level 4 Abrasion Resistance
- Color-coded overcast reduces fraying and acts as a visual aid in sizing
- Machine washable for longer service life

APPLICATIONS

Construction, waste removal, transportation, and cold storage applications.

AVAILABLE STYLES

Size	7	8	9	10	11
Item Number	GP600W7	GP600W8	GP600W9	GP600W10	GP600W11

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	3

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Sarah Anderson	Date	8/10/2015	
Revised By	Brittany Cohen	Date	07/11/2017	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.