

Product Specifications

Style #GPD248



D-ROC®

Magid® D-ROC® GPD248 Hyperon® 15-Gauge TriTek Palm® Coated Work Glove – Cut Level A2

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	15-gauge, seamless machine knit
Composition	Hyperon® shell; TriTek Palm® coating
Color(s)	Hi-viz yellow shell; black palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS

- 15-gauge Hyperon® shell delivers breathability, comfort, and cut protection
- Flexible dual-layer TriTek Palm® coating strengthens grip and minimizes saturation in heavy liquid and oil applications
- Resilient TriTek Palm coating provides over 2X the abrasion resistance of other coatings for unbeatable durability while maintaining extreme dexterity
- Touchscreen compatible to maintain user safety while operating electronic devices
- High-visibility shell color enhances worker protection and compliance
- Shield graphic is color-coded by cut level to easily identify cut protection from a distance
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- Machine washable for longer service life
- ANSI Level A2 Cut Resistance, ANSI Level 5 Abrasion Resistance, ANSI Level 4 Puncture Resistance

APPLICATIONS

Assembly or movement of large, bulky, or heavy objects with sharp edges, Automotive Manufacturing, Metal Fabrication, Appliance Manufacturing, Aerospace Manufacturing, and Glass Fabrication.

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item #	GPD2485	GPD2486	GPD2487	GPD2488	GPD2489	GPD24810	GPD24811	GPD24812
FUNCTIONAL PERFORMANCE								
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria								
Test Method					Clause	ANSI Level		
ASTM F2992-15 Cut Resistance					-	A2		
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)					-	5		
ANSI/ISEA: 105-2011 Puncture Resistance (other than hypodermic needle)					6.4	4		
SERVICE LIFE								
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.								
Critical Defects	Holes/tears							
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects							
LAUNDERING GUIDELINES								
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.								
GENERAL INFORMATION								
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.								

Originator	Scott Daigle	Date	12/9/2019		
Revised By	Dana Cornish	Date	4/20/2022	Revision #	2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD