

Product Specifications

Item #GPD252AW



**Magid® Griffin Gear™ Hyperon® Blended
Polyurethane Palm Coated Work Gloves – Cut Level
A2**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	15-gauge, seamless machine knit shell, no imprint on back
Composition	Hyperon® shell; polyurethane palm coating
Color(s)	Salt & pepper shell, black coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), gray (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	PR
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS	
• Durable 15 gauge Hyperon® blended shell delivers breathability, comfort and 360° cut protection • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Affordable protection to meet the needs of any safety program • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A2 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 2 Puncture Resistance	

APPLICATIONS	
Assembly, machine, automotive manufacturing, metal handling, maintenance and construction.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD252AW5	GPD252AW6	GPD252AW7	GPD252AW8	GPD252AW9	GPD252AW10	GPD252AW11	GPD252AW12

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)		4
EN 388:2003 Puncture Resistance	-	2

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects Holes/tears

Major Defects Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Scott Daigle	Date	1/12/2017	
Revised By	Scott Daigle	Date	12/18/2020	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.