

Product Specifications

Style #GPD261



D-ROC®
by Magid

**Magid® D-ROC® Affordable Hi-Viz DuraBlend®
Polyurethane Palm Coated Work Glove – Cut Level A2**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit
Composition	DuraBlend™ shell; polyurethane palm coating
Color(s)	Hi-viz yellow shell; grey palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case
FEATURES & BENEFITS	
• Form-fitting DuraBlend® shell delivers breathability, comfort, and 360° cut protection • High-visibility color enhances worker protection and ensures worker compliance • Polyurethane palm coating maintains dexterity while delivering excellent grip • Affordable protection to meet the needs of any safety program • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Machine washable for longer service life • ANSI Level A2 Cut Resistance, ANSI Level 4 Abrasion Resistance, and ANSI Level 2 Puncture Resistance	
APPLICATIONS	
Assembly, appliance manufacturing, automotive, construction, maintenance, material handling, and metal handling.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Part Number	GPD2615	GPD2616	GPD2617	GPD2618	GPD2619	GPD26110	GPD26111	GPD26112

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	2

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	11/9/2018	
Revised By	Scott Daigle	Date	1/7/2019	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.