

Product Specifications

Item #GPD282



D-ROC®
by Magid

Magid® D-ROC® Super Soft 15-Gauge Polyurethane Palm Work Gloves – Cut Level A2

For jobs that involve precision handling of sharp materials, the super soft GPD282 Hyperon™ work gloves combine ultra-comfortable, cool-to-the-touch dexterity with 360° ANSI level A2 cut protection.

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	Double-knit, 15-gauge seamless machine knit shell
Composition	Hyperon™ fiber blended shell; polyurethane palm coating
Color(s)	Salt & pepper shell, grey palm coating
Size(s)	4 – 12
Cuff/Finish	Knit wrist cuff with color-coded elasticized overcast: yellow (4), purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS

- Polyurethane palm coating maintains dexterity while delivering excellent grip
- Durable 15-gauge Hyperon™ shell delivers breathability, comfort, and 360° cut protection
- Premium Hyperon™ form-fitting shell contours to the hand for a comfortable fit and maximum dexterity
- Shield graphic is color-coded by cut level to easily identify cut protection from a distance
- ANSI Level 6 abrasion resistance extends the life of the glove
- Color-coded overcast acts as a visual aid for sizing and helps prevent fraying
- Machine washable for longer service life
- Silicone-free
- ANSI Level A2 Cut Resistance, ANSI Level 6 Abrasion Resistance, and ANSI Level 3 Puncture Resistance

APPLICATIONS

Assembly, machine, automotive manufacturing, metal handling, maintenance and construction.

AVAILABLE STYLES									
Size	4	5	6	7	8	9	10	11	12
Item Number	GPD2824	GPD2825	GPD2826	GPD2827	GPD2828	GPD2829	GPD28210	GPD28211	GPD28212

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)		6
EN 388:2003 Puncture Resistance	-	3

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Scott Daigle	Date	2/28/2018	
Revised By	Scott Daigle	Date	4/5/2018	Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.