

Product Specifications

Style #GPD295



D-ROC®
by Magid

Double-Dipped Three-Quarter Coated NitrilX® Grip Technology Palm Work Gloves – Cut Level A2

For customers who work with sharp materials where fluids may be present, the GPD295 Hyperon™ work gloves provide ultra-comfortable 360° ANSI level A2 cut protection with double-dipped three-quarter coating for long-lasting protection that protects against liquids, oils, and solvents while maintaining dexterity.

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit
Composition	Hyperon™ shell; NitrilX® Grip Technology palm coating; nitrile three-quarter undercoat
Color(s)	Grey shell; black palm coating, blue three-quarter undercoat
Size(s)	6-11
Cuff/Finish	Color-coded elasticized overcast: grey (6), light blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS

- Ultra-lightweight, form-fitting 18-gauge Hyperon™ shell delivers bare hand dexterity and cool comfort plus 360° cut protection
- Three-quarter undercoat protects against liquids, oils, and solvents
- Double-Dipped NitrilX® Grip Technology Palm Coating delivers rock-solid grip in oily applications, enhanced abrasion resistance and increases wear life
- Dark color hides dirt and grime to extend worker wear time
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- Machine washable for longer service life
- ANSI Level A2 Cut Resistance, ANSI Level 3 Puncture Resistance

APPLICATIONS

Appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping.

AVAILABLE STYLES

Size	6	7	8	9	10	11
Part Number	GPD2956	GPD2957	GPD2958	GPD2959	GPD29510	GPD29511

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A2
ANSI/ISEA: 105-2011 Puncture Resistance	6.4	3
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.		

Originator	Scott Daigle	Date	9/20/2017	
Revised By	Scott Daigle	Date	4/19/2018	Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

