

Product Specifications

Item #GPD412



D-ROC®

Magid® D-ROC® GPD412 21G
Ultra-Thin Polyurethane
Palm Coated Work Gloves –
Cut Level A4



PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	21-gauge, seamless machine knit shell
Composition	21G fiber blend shell; polyurethane palm coating
Color(s)	Grey
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), gray (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	PR
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS

- Ultra-thin 21-gauge knit construction delivers revolutionary bare-hand dexterity and tactile sensitivity
- Specially engineered 21G lightweight fiber technology provides extreme comfort and A4 cut resistance
- Polyurethane palm coating maintains dexterity while delivering an excellent grip
- Touchscreen compatible work gloves maintain user safety while operating electronic devices
- Shield graphic is color-coded by cut level to easily identify cut protection from a distance
- Nitrile reinforced thumb saddle enhances durability at a critical wear point
- Color-coded overcast acts as a visual aid for sizing and reduced fraying
- Machine washable for longer service life
- ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Level 3 Puncture Resistance

APPLICATIONS

Material handling, electrical contractors, assembly line, mechanics repair, maintenance and shipping & receiving. Especially relevant for jobs that require handling of small parts and hand dexterity.

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	GPD4125	GPD4126	GPD4127	GPD4128	GPD4129	GPD41210	GPD41211	GPD41212

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A4
ASTM D338-10 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Kim Schultz	Date	6/13/2023	
Revised By	Kim Schultz	Date	11/27/2023	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD