

Product Specifications

Item #GPD456



Magid® Griffin Gear™ 13 Gauge Foam Nitrile Coated Work Glove – Cut Level A4

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	DuraBlend™ shell; foam nitrile palm coating
Color(s)	Salt & pepper shell; black palm coating
Size(s)	5-12
Cuff/Finish	Color-coded elasticized overcast: purple (5), gray (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case
FEATURES & BENEFITS	
• 13 gauge DuraBlend™ shell delivers breathability, comfort, and 360° cut protection • Foam nitrile palm coating channels oil away for a superb grip in light oil applications • Affordable protection to meet the needs of any safety program • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Machine washable for longer service life • ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance, and ANSI Level 4 Puncture Resistance	
APPLICATIONS	
Appliance manufacturing, automotive, construction, glass handling, machining, metal handling, metal stamping, and paper production	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD4565	GPD4566	GPD4567	GPD4568	GPD4569	GPD45610	GPD45611	GPD45612

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
Cut Resistance	-	A4
Abrasion Resistance	-	4
Puncture Resistance	-	4

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

Originator	Scott Daigle	Date	10/24/2018	
Revised By	Scott Daigle	Date	12/18/2020	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.