

Product Specifications

Style #GPD469OSK



D-ROC®
by Magid

**Magid® D-ROC® Hi-Vis Foam Nitrile Palm Coated
Work Gloves with Reinforced Thumb Saddle – Cut
Level A4**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit, thumb saddle, touchscreen compatible
Composition	Hyperon™ shell; foam nitrile palm coating, nitrile-reinforced thumb saddle
Color(s)	Orange shell; orange palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
• Ultra-lightweight, form-fitting 18-gauge Hyperon™ shell delivers bare hand dexterity and cool comfort plus 360° cut protection • Foam nitrile palm coating adds durability and ensures superb grip while channeling away oils and liquids • Touchscreen compatible • Nitrile-reinforced thumb saddle coating delivers up to 1.7 times the abrasion resistance at critical wear point • High-visibility color enhances worker protection and compliance • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 4 Puncture Resistance	

APPLICATIONS	
Door and wood framing, glass installation, knife handling, maintenance operations, paper slitting, sharp, small part handling, sheet metal press and small part stamping applications.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD469OSK5	GPD469OSK6	GPD469OSK7	GPD469OSK8	GPD469OSK9	GPD469OSK10	GPD469OSK11	GPD469OSK12
FUNCTIONAL PERFORMANCE								
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria								
Test Method						Clause	ANSI Level	
ASTM F2992-15 Cut Resistance						-	A4	
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)						-	4	
EN 388:2003 Puncture Resistance						6.4	4	
SERVICE LIFE								
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.								
Critical Defects		Holes/tears						
Major Defects		Dimensional or weight nonconformance, discoloration, other fabric defects						
LAUNDERING GUIDELINES								
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.								
GENERAL INFORMATION								
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.								

Originator	Scott Daigle	Date	11/9/2021	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.