

Product Specifications

Style #GPD469YOK



D-ROC®
by Magid

**Magid® D-ROC® Hi-Vis Foam Nitrile Dotted Palm
Coated Work Gloves with Reinforced Thumb Saddle –
Cut Level A4**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit, thumb saddle, touchscreen compatible
Composition	Hyperon™ shell; foam nitrile palm coating, silicone dots on palm, nitrile-reinforced thumb saddle
Color(s)	Hi-vis yellow shell; hi-vis orange palm coating, hi-vis orange dots on palm
Size(s)	6 – 12
Cuff/Finish	Color-coded elasticized overcast: grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)
FEATURES & BENEFITS	
• Ultra-lightweight, form-fitting 18-gauge Hyperon™ shell delivers bare hand dexterity and cool comfort plus 360° cut protection • Foam nitrile palm coating with silicone dots adds durability and ensures superb grip while channeling away oils and liquids • Touchscreen compatible • Nitrile-reinforced thumb saddle coating delivers up to 1.7 times the abrasion resistance at critical wear point • High-visibility color enhances worker protection and compliance • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 4 Puncture Resistance	
APPLICATIONS	
Door and wood framing, glass installation, knife handling, maintenance operations, paper slitting, sharp, small part handling, sheet metal press and small part stamping applications.	

AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Item Number	GPD469YOK6	GPD469YOK7	GPD469YOK8	GPD469YOK9	GPD469YOK10	GPD469YOK11	GPD469YOK12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A4
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	12/1/2021	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.