

Product Specifications

Style #GPD486



D-ROC®

Magid® D-ROC® AeroDex® 18-Gauge Extremely Lightweight Foam Nitrile Coated Work Glove – Cut Level A5

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit
Composition	AeroDex® shell; foam nitrile palm coating
Color(s)	Blue shell; black palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS

- AeroDex® engineered yarn delivers extremely lightweight A5 cut resistance that is 50% lighter than a traditional HPPE of the same cut level
- 18-gauge AeroDex shell delivers unmatched dexterity & tactile sensitivity making it agile enough for any job
- AeroDex is specially engineered to make your hands feel cooler than a comparable cut resistant glove
- Premium ultra-thin foam nitrile palm coating channels oil away for a superb grip in light oil applications
- Touchscreen compatible to maintain user safety while operating electronic devices
- Shield graphic is color-coded by cut level to easily identify cut protection from a distance
- Color-coded overcast acts as a visual aid for sizing and helps prevent fraying
- Machine washable for longer service life
- NEAT Tested
- ANSI Level A5 Cut Resistance, ANSI Level 5 Abrasion Resistance, ANSI Level 3 Puncture Resistance

APPLICATIONS

Appliance manufacturing, automotive, construction, glass handling, machining, metal handling, metal stamping, maintenance, assembly

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	GPD4865	GPD4866	GPD4867	GPD4868	GPD4869	GPD48610	GPD48611	GPD48612

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	5
ANSI/ISEA: 105-2011 Puncture Resistance	6.4	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	9/24/2019		
Revised By	Dana Cornish	Date	05/16/2022	Revision #	1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD