

Product Specifications

Style #GPD495



D-ROC®
by Magid

**Magid® D-ROC® Hyperon® 13-Gauge Double-Dipped
Three-Quarter Nitrile Grip Technology Coated Work
Glove – Cut Level A4**

PRODUCT DESCRIPTION							
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated						
Construction/Design	13-gauge, seamless machine knit						
Composition	Hyperon® shell; NitrIX® Grip Technology palm coating; nitrile three-quarter undercoat						
Color(s)	Grey shell; black palm coating, blue three-quarter undercoat						
Size(s)	6-12						
Cuff/Finish	Color-coded elasticized overcast: grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)						
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)						
Packaging	12 pairs per inner pack, 144 pairs per case						
FEATURES & BENEFITS							
13-gauge Hyperon® shell is cool and lightweight for incredible comfort and cut protection - Three-quarter nitrile undercoat protects against liquids, oils, and solvents - NitrIX® Grip Technology Palm Coating delivers rock-solid grip in oily applications, enhanced abrasion resistance and increases wear life - Color-coded overcast acts as a visual aid for sizing and reduces fraying - Machine washable for longer service life - ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Level 4 Puncture Resistance							
APPLICATIONS							
Appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping							
AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Part Number	GPD4956	GPD4957	GPD4958	GPD4959	GPD49510	GPD49511	GPD49512

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A4
ANSI/ISEA: 105-2011 Puncture Resistance	6.4	4
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)		4
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.		

Originator	Scott Daigle	Date	2/4/2020		
Revised By	Brittany Cohen	Date	9/22/2020	Revision #	1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.