

Product Specifications

Item #GPD510



Magid® D-ROC® Hyperon® Blended Polyurethane Palm Coated Work Gloves - Cut Level 2

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit shell
Composition	Hyperon® fiber blended shell; polyurethane palm coating
Color(s)	Salt & pepper shell, gray coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), gray (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	PR
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS

- Durable Hyperon® blended shell delivers breathability, comfort and cut protection
- Polyurethane palm coating maintains dexterity while delivering an excellent grip
- Affordable protection to meet the needs of any safety program
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- Machine washable for longer service life
- ANSI Level 2 Cut Resistance, ANSI Level 6 Abrasion Resistance and ANSI Level 5 Puncture Resistance

APPLICATIONS

Assembly, Appliance Manufacturing, Automotive, Construction Maintenance, Material Handling and Metal Handling.

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	GPD5105	GPD5106	GPD5107	GPD5108	GPD5109	GPD51010	GPD51011	GPD51012

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	6
ANSI/ISEA : 105-2011 Puncture Resistance	6.4	5

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Sarah Anderson	Date	9/30/2015		
Revised By	Dana Cornish	Date	4/20/2022	Revision #	2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD