

Product Specifications

Item #GPD514



D-ROC®
by Magid

Magid® D-ROC® HPPE Blended Polyurethane Palm Coated Work Gloves - Cut Level A4

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit shell
Composition	Hyperon® fiber blended shell; polyurethane palm coating
Color(s)	Salt & pepper shell, gray coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), gray (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	PR
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS

- Durable Hyperon® blended shell delivers breathability, comfort, and cut protection
- Polyurethane palm coating maintains dexterity while delivering an excellent grip
- Affordable protection to meet the needs of any safety program
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- PPG Tested
- Machine washable for longer service life
- ANSI Level A4 Cut Resistance, ANSI Level 5 Abrasion Resistance and ANSI Level 5 Puncture Resistance under the ANSI/ISEA 105-2016 standard

APPLICATIONS

Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling and Metal Stamping

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	GPD5145	GPD5146	GPD5147	GPD5148	GPD5149	GPD51410	GPD51411	GPD51412

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A4
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	5
EN 388:2003 Puncture Resistance		5

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistance	-	4

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Sarah Anderson	Date	9/30/2015		
Revised By	Dana Cornish	Date	05/16/2022	Revision #	1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD