

Product Specifications

Item #GPD520B



D-ROC®
by Magid

Magid® D-ROC® Polyurethane Palm Coated Work Gloves – Cut Level A3

For jobs that involve handling sharp or rough materials, the GPD520B work glove is Magid's most affordable ANSI Cut A3 glove and one of the few available in black, which hides dirt and extends the overall life of the glove.

PRODUCT DESCRIPTION								
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated							
Construction/Design	15-gauge, seamless machine knit							
Composition	DuraBlend™ shell; polyurethane palm coating							
Color(s)	Black shell; black palm coating							
Size(s)	5 – 12							
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)							
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)							
Packaging	12 pairs per inner pack, 12 inner packs per case							
FEATURES & BENEFITS								
• Most affordable cut-resistant glove to meet the needs of any safety program • ANSI Level A3 Cut Resistance, Level 4 Abrasion Resistance and Level 2 Puncture Resistance • Black color hides dirt extends worker wear time • Form-fitting DuraBlend™ shell delivers breathability, comfort and 360° cut protection • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life								
APPLICATIONS								
Assembly, appliance manufacturing, automotive assembly, maintenance and material handling.								
AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD520B5	GPD520B6	GPD520B7	GPD520B8	GPD520B9	GPD520B10	GPD520B11	GPD520B12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A3
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	2
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.		

Originator	Sarah Anderson	Date	03/03/15	
Revised By	Scott Daigle	Date	3/29/2017	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

