

Product Specifications

Style #GPD525HV



D-ROC[®]
by Magid

Magid[®] D-ROC[®] High Visibility Polyurethane Palm Coated Work Glove – Cut Level A3

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	15-gauge, seamless machine knit
Composition	DuraBlend [®] shell; polyurethane palm coating
Color(s)	Hi-viz yellow shell; hi-viz yellow palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS

- High-visibility color enhances worker protection and ensures worker compliance
- Form-fitting DuraBlend shell delivers breathability, comfort, and cut protection
- Polyurethane palm coating maintains dexterity while delivering an excellent grip
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- Machine washable for longer service life
- NEAT Tested
- ANSI Level A3 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 2 Puncture Resistance

APPLICATIONS

Assembly, appliance manufacturing, automotive assembly, maintenance and material handling.

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Part Number	GPD525HV5	GPD525HV6	GPD525HV7	GPD525HV8	GPD525HV9	GPD525HV10	GPD525HV11	GPD525HV12

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A3
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	2

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Sarah Anderson	Date	09/05/2014	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD