

Product Specifications

Item #GPD530RT



Magid® D-ROC® Polyurethane Palm Coated Work Glove with Reinforced Thumb Saddle – Cut Level A2

For customers who work with sharp materials and need additional durability at a critical wear point, the GPD530RT Hyperon™ work gloves provide long-lasting, comfortable hand protection with a reinforced thumb saddle.

PRODUCT DESCRIPTION							
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated						
Construction/Design	13-gauge, seamless machine knit, reinforced thumb saddle						
Composition	Hyperon™ shell; polyurethane palm coating; nitrile reinforcement on thumb saddle						
Color(s)	Salt & pepper shell; black palm coating, blue nitrile reinforcement on thumb saddle						
Size(s)	6 – 12						
Cuff/Finish	Color-coded overcast: white (6), green (7), brown (8), yellow (9), black (10), grey (11), blue (12)						
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)						
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)						
FEATURES & BENEFITS							
• Durable 13 gauge Hyperon™ shell delivers breathability, comfort and 360° cut protection • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Blue nitrile-reinforced thumb saddle coating delivers up to 40 times the abrasion resistance at critical wear point • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A2 Cut Resistance							
APPLICATIONS							
Assembly, machining, automotive manufacturing, metal handling, maintenance and construction							
AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Item Number	GPD530RT6	GPD530RT7	GPD530RT8	GPD530RT9	GPD530RT10	GPD530RT11	GPD530RT12
FUNCTIONAL PERFORMANCE							

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistance	-	A2
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.		

Originator	Scott Daigle	Date	4/27/2017	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.