

Product Specifications

Style #GPD545HV



D-ROC®

Magid® D-ROC® High Visibility Polyurethane Palm Coated Work Glove – Cut Level A4

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® blended shell; polyurethane palm coating
Color(s)	Hi-viz yellow shell; hi-viz yellow palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS	
• High-visibility color enhances worker protection and ensures worker compliance • Hyperon® shell delivers cool comfort and dependable cut protection • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 4 Puncture Resistance under the ANSI/ISEA 105-2016 standard	

APPLICATIONS	
Appliance and automotive manufacturing, construction, metal handling, metal fabrication and metal stamping.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Part Number	GPD545HV5	GPD545HV6	GPD545HV7	GPD545HV8	GPD545HV9	GPD545HV10	GPD545HV11	GPD545HV12

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A4
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	4

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

Test Method	Clause	EN Level
Blade Cut Resistance	6.2	5

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Sarah Anderson	Date	09/05/2014	
Revised By	Dana Cornish	Date	11/18/2021	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.