

Product Specifications

Item #GPD546



D-ROC®
by Magid

**Magid® D-ROC® Lightweight Polyurethane Palm
Coated Work Glove – Cut Level A2**

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® shell; polyurethane palm coating
Color(s)	Salt & pepper shell; grey palm coating
Size(s)	5 - 11
Cuff/Finish	Color-coded overcast: blue (5), white (6), green (7), brown (8), yellow (9), black (10), white (11)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS

- Durable 13- gauge Hyperon® shell delivers breathability, comfort, and cut protection
- Hyperon® blend offers ANSI Level A2 cut protection
- Polyurethane palm coating channels away oils and ensures a secure grip
- Used in areas where a high level of dexterity is required in addition to cut/laceration protection
- Color-coded overcast reduces fraying and acts as a visual aid for sizing
- Machine washable for longer service life
- PPG and NEAT Tested
- ANSI Level A2 Cut Resistance, ANSI Level 6 Abrasion Resistance and ANSI Level 3 Puncture Resistance under the ANSI/ISEA 105-2016 standard

APPLICATIONS

Assembly, automotive manufacturing, appliance industry, metal handling, maintenance and construction

AVAILABLE STYLES

Size	5	6	7	8	9	10	11
Part Number	GPD5465	GPD5466	GPD5467	GPD5468	GPD5469	GPD54610	GPD54611

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria**

Test	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A2
ASTM D3389 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	6
EN 388: Puncture Resistance	6.4	3

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

Test Method	Clause	EN Level
Blade Cut Resistance	6.2	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

Originator	Adam Cohen	Date	10/05/2003	
Revised By	Kim Schultz	Date	02/13/2026	Revision # 10

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.