

Product Specifications

Style #GPD565HV



D-ROC®
by Magid

**Magid® D-ROC® 13 Gauge Hi-Vis NitriX® Grip
Technology Coated Work Glove – Cut Level A4**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® blended shell; NitriX® Grip Technology palm coating
Color(s)	Hi-viz yellow shell; hi-viz orange palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case
FEATURES & BENEFITS	
• 13-Gauge Hyperon® shell delivers breathability, comfort and 360° cut protection • NitriX® Grip Technology palm coating delivers rock-solid grip in oily applications, enhanced abrasion resistance and increased wear life • High-visibility color enhances worker protection in low-light conditions and ensures worker compliance • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Machine washable for longer service life • ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Puncture Level 4 Resistance	
APPLICATIONS	
Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling, Metal Stamping, Paper Production	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD565HV5	GPD565HV6	GPD565HV7	GPD565HV8	GPD565HV9	GPD565HV10	GPD565HV11	GPD565HV12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A4
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Brittany Cohen	Date	11/5/2019	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.