

Product Specifications

Style #GPD575HV



D-ROC®
by Magid

**Magid® D-ROC® Lightweight Hi-Viz Polyurethane
Palm Coated Work Gloves – Cut Level A7**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® and steel blended shell; polyurethane palm coating
Color(s)	Hi-viz yellow shell; hi-viz yellow palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)
FEATURES & BENEFITS	
• Lightweight, form-fitting 13-gauge Hyperon® and steel blended shell delivers bare hand dexterity and cool comfort plus 360° cut protection • Polyurethane palm coating maintains dexterity while delivering excellent grip • High-visibility color enhances worker protection and compliance • Touchscreen compatible • Color-coded overcast acts as a visual aid for sizing and reduces fraying • PPG Tested • Machine washable for longer service life • ANSI Level A7 Cut Resistance, ANSI Level 6 Abrasion Resistance and ANSI Level 5 Puncture Resistance	
APPLICATIONS	
Appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD575HV5	GPD575HV6	GPD575HV7	GPD575HV8	GPD575HV9	GPD575HV10	GPD575HV11	GPD575HV12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A7
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	6
EN 388:2003 Puncture Resistance	6.4	5

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	9/1/2017	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.