

Product Specifications

Item #GPD580



D-ROC®
by Magid

**Magid® D-ROC® Ultra-lightweight Polyurethane
Palm Coated Work Glove – Cut Level A2**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit
Composition	Hyperon® shell; polyurethane palm coating
Color(s)	Salt & pepper shell; black palm coating
Size(s)	6 – 12
Cuff/Finish	Color-coded overcast: grey (6), blue (7), green (8), red (9), black (10), yellow (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
• Ultra-lightweight, form-fitting 18-gauge construction delivers exceptional comfort and the dexterity with cut protection • Hyperon® shell offers high ANSI Level A2 cut protection • Polyurethane palm coating channels away oils and ensures a secure grip • Dark color hides dirt and grime to extend wear • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • PPG Tested • ANSI Level A2 Cut Resistance and ANSI Level 4 Abrasion Resistance under the ANSI/ISEA 105-2016 standard	

APPLICATIONS	
Assembly, machining, automotive manufacturing, metal handling, maintenance and construction	

AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Part Number	GPD5806	GPD5807	GPD5808	GPD5809	GPD58010	GPD58011	GPD58012

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	3

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

Test Method	Clause	EN Level
Blade Cut Resistance	6.2	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

Originator	Efi Vrshek	Date	3/26/2013	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 5

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.