

Product Specifications

Item #GPD583



D-ROC®
by Magid

Magid® D-ROC® GPD583 18-Gauge GPD583 Hyperon® Blend Foam Nitrile Palm Coated Work Glove - ANSI Cut Level A3

PRODUCT DESCRIPTION

| | |
|------------------------|--|
| Product Classification | Special Purpose Work glove – Cut Resistant, coated |
| Construction/Design | 18-gauge, seamless machine knit |
| Composition | Hyperon™ shell; foam nitrile palm coating |
| Color(s) | Salt & pepper shell; black palm coating |
| Size(s) | 6-11 |
| Cuff/Finish | Color-coded elasticized overcast: white (6), green (7), brown (8), yellow (9), black (10), grey (11) |
| Unit of Measure | Pair (must be ordered in multiples of 12 pairs) |
| Packaging | 12 pairs per inner pack, 12 inner packs per case |

FEATURES & BENEFITS

- Durable 18-gauge Hyperon® shell delivers breathability, comfort, and 360° cut protection
- Hyperon® shell offers high ANSI Level A3 cut protection
- Soft, flexible foam nitrile coating ensures great grip of small parts even in wet/oily conditions
- Dark color hides dirt and grime to extend wear
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- ANSI Level A3 Cut Resistance and ANSI Level 4 Abrasion Resistance

APPLICATIONS

Assembly, machine, automotive manufacturing, metal handling, maintenance, and construction

AVAILABLE STYLES

| Size | 6 | 7 | 8 | 9 | 10 | 11 |
|-------------|---------|---------|---------|---------|----------|----------|
| Item Number | GPD5836 | GPD5837 | GPD5838 | GPD5839 | GPD58310 | GPD58311 |

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria

| Test Method | Clause | ANSI Level |
|---|--------|------------|
| ASTM F2992 Cut Resistance | - | A3 |
| ASTM D3389 Abrasion Resistance (Using H-18 wheel with a 1000-gram load) | - | 4 |
| EN 388 Puncture Resistance | - | 4 |

European Standard: EN 388 Protective Gloves Against Mechanical Risk

| Test Method | Clause | EN Level |
|----------------------|--------|----------|
| Blade Cut Resistance | 6.2 | 4 |

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

| | |
|------------------|---|
| Critical Defects | Holes/tears |
| Major Defects | Dimensional or weight nonconformance, discoloration, other fabric defects |

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

| | | | | |
|------------|----------------|------|------------|--------------|
| Originator | Brenda Sanchez | Date | 05/01/2015 | |
| Revised By | Kim Schultz | Date | 02/28/2024 | Revision # 3 |

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD