

# Product Specifications

Item #GPD584



## D-ROC®

Magid® D-ROC® GPD584 18-Gauge Hyperon® Blend  
Polyurethane Palm Coated Work Glove – Cut Level A4

| PRODUCT DESCRIPTION    |                                                                                                                           |
|------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Product Classification | Special Purpose Work glove – Cut Resistant, coated                                                                        |
| Construction/Design    | 18-gauge, seamless machine knit                                                                                           |
| Composition            | Hyperon® shell; polyurethane palm coating                                                                                 |
| Color(s)               | Salt & pepper shell; black palm coating                                                                                   |
| Size(s)                | 5-12                                                                                                                      |
| Cuff/Finish            | Color-coded elasticized overcast: purple (5), gray (6), blue (7), green (8), red (9), black (10), yellow (11), white (12) |
| Unit of Measure        | Pair (must be ordered in multiples of 12 pairs)                                                                           |
| Packaging              | 12 pairs per inner pack, 12 inner packs per case                                                                          |

| FEATURES & BENEFITS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <ul style="list-style-type: none"><li>• Ultra-lightweight, form-fitting 18-gauge construction delivers bare hand dexterity and excellent comfort</li><li>• Hyperon® shell offers ANSI Cut Level A4 protection</li><li>• Polyurethane palm coating maintains dexterity while delivering excellent grip</li><li>• Salt and pepper color hides dirt and grime to extend wear</li><li>• Color-coded overcast acts as a visual aid for sizing and reduces fraying</li><li>• PPG Tested</li><li>• ANSI Level A4 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 4 Puncture Resistance</li></ul> |  |

| APPLICATIONS                                                                              |  |
|-------------------------------------------------------------------------------------------|--|
| Assembly, machine, automotive manufacturing, metal handling, maintenance and construction |  |

| AVAILABLE STYLES |         |         |         |         |         |          |          |          |
|------------------|---------|---------|---------|---------|---------|----------|----------|----------|
| Size             | 5       | 6       | 7       | 8       | 9       | 10       | 11       | 12       |
| Item Number      | GPD5845 | GPD5846 | GPD5847 | GPD5848 | GPD5849 | GPD58410 | GPD58411 | GPD58412 |

| FUNCTIONAL PERFORMANCE                                                                                                                                                                                                |                                                                           |            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|------------|
| US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria                                                                                                                     |                                                                           |            |
| Test Method                                                                                                                                                                                                           | Clause                                                                    | ANSI Level |
| Cut Resistance                                                                                                                                                                                                        | -                                                                         | A4         |
| Abrasion Resistance                                                                                                                                                                                                   | -                                                                         | 4          |
| Puncture Resistance                                                                                                                                                                                                   | -                                                                         | 4          |
| European Standard: EN 388:2003 Protective Gloves Against Mechanical Risk                                                                                                                                              |                                                                           |            |
| Test Method                                                                                                                                                                                                           | Clause                                                                    | EN Level   |
| Blade Cut Resistance                                                                                                                                                                                                  | 6.2                                                                       | TBD        |
| SERVICE LIFE                                                                                                                                                                                                          |                                                                           |            |
| The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.       |                                                                           |            |
| Critical Defects                                                                                                                                                                                                      | Holes/tears                                                               |            |
| Major Defects                                                                                                                                                                                                         | Dimensional or weight nonconformance, discoloration, other fabric defects |            |
| LAUNDERING GUIDELINES                                                                                                                                                                                                 |                                                                           |            |
| Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight. |                                                                           |            |

|            |                |      |            |              |
|------------|----------------|------|------------|--------------|
| Originator | Sarah Anderson | Date | 03/07/2016 |              |
| Revised By | Kim Schultz    | Date | 05/16/2024 | Revision # 3 |

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

