

Product Specifications

Style #GPD585



D-ROC®
by Magid

Magid® D-ROC® 13-Gauge Non-Marring Crinkle Latex Coated Cut Resistant Work Glove - Cut Level A5

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® shell; non-marring crinkle latex palm coating
Color(s)	Grey/red shell; blue palm coating
Size(s)	5-12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS

- 13-Gauge Hyperon® shell delivers breathability, comfort, cut protection
- Non-marring crinkle latex coating is 2 times more durable than traditional latex
- Soft and flexible coating reduces hand fatigue without sacrificing grip or durability
- Nitrile reinforced thumb saddle enhances durability at a critical wear point
- Color-coded overcast acts as a visual aid for sizing and helps prevent fraying
- Shield graphic is color-coded by cut level to easily identify cut protection from a distance
- Machine washable for longer service life
- NEAT tested
- ANSI Level A5 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Puncture Level 4 Resistance

APPLICATIONS

Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling, Metal Stamping, Paper Production

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD5855	GPD5856	GPD5857	GPD5858	GPD5859	GPD58510	GPD58511	GPD58512

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A5
ASTM D3389-10 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	12/16/2022	
Revised By	Kim Schultz	Date	08/01/2023	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD