

Product Specifications

Item #GPD586



**Magid® D-ROC® GPD586 18-Gauge Hyperon® Blend
Foam Nitrile Palm Coated Work Glove – Cut Level 4**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work glove – Cut Resistant, coated
Construction/Design	18-gauge, seamless machine knit
Composition	Hyperon® blended shell; foam nitrile palm coating
Color(s)	Salt & pepper shell; black palm coating
Size(s)	5-12
Cuff/Finish	Color-coded elasticized overcast: purple (5), gray (6), blue (7), green (8), red (9), black (10), yellow (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS	
• Durable 18-gauge Hyperon® shell delivers breathability, comfort, and cut protection • Hyperon® shell offers ANSI Cut Level 4 protection • Soft, flexible foam nitrile palm coating ensures superb grip while channeling away oils and liquids • Salt and pepper color hides dirt and grime to extend wear • Color-coded overcast acts as a visual aid for sizing and reduces fraying • PPG and NEAT Tested • ANSI Level 4 Cut Resistance, ANSI Level 5 Abrasion Resistance and ANSI Level 4 Puncture Resistance	

APPLICATIONS	
Assembly, machine, automotive manufacturing, metal handling, maintenance and construction	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD5865	GPD5866	GPD5867	GPD5868	GPD5869	GPD58610	GPD58611	GPD58612

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
Cut Resistance	-	4
Abrasion Resistance	-	5
Puncture Resistance	-	4
European Standard: EN 388:2003 Protective Gloves Against Mechanical Risk		
Test Method	Clause	EN Level
Blade Cut Resistance	6.2	5
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		

Originator	Jennifer Walrich	Date	09/19/2016	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

