

Product Specifications

Style #GPD590



D-ROC®
by Magid

**Magid® D-ROC® Hyperon® Polyurethane Palm
Coated Work Glove – Cut Level A5**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	10-gauge, seamless machine knit
Composition	Hyperon® shell; polyurethane palm coating
Color(s)	Salt & pepper shell; grey palm coating
Size(s)	4-12
Cuff/Finish	Color-coded overcast: yellow (4), purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
<ul style="list-style-type: none">• Durable Hyperon® blended shell delivers breathability, comfort and cut protection• Polyurethane palm coating maintains dexterity while delivering an excellent grip• Shield graphic is color-coded by cut level to easily identify cut protection from a distance• Color-coded overcast acts as a visual aid for sizing and reduces fraying• Machine washable for longer service life• PPG and NEAT Tested• ANSI Level A5 Cut Resistance, ANSI Level 6 Abrasion Resistance and ANSI Level 3 Puncture Resistance	

APPLICATIONS	
Assembly, automotive manufacturing, appliance industry, metal stamping, metal fabrication, shipping and receiving, material handling and general maintenance	

AVAILABLE STYLES									
Size	4	5	6	7	8	9	10	11	12
Part Number	GPD5904	GPD5905	GPD5906	GPD5907	GPD5908	GPD5909	GPD59010	GPD59011	GPD59012

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	6
EN 388:2003 Puncture Resistance	6.4	3

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	4

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks		
Test Method	Clause	EN Level
Blade Cut Resistance	6.2	5

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

Originator	Jim Pump	Date	09/27/2011	
Revised By	Dana Cornish	Date	5/16/2022	Revision # 14

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.