

Product Specifications

Style #GPD590B



D-ROC®
by Magid

Magid® D-ROC® Black Hyperon® Polyurethane Palm
Coated Work Gloves – Cut Level A5

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	10-gauge, seamless machine knit
Composition	Hyperon® shell; polyurethane palm coating
Color(s)	Black shell; black palm coating
Size(s)	5 - 11
Cuff/Finish	Color-coded overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
• Black color hides dirt and grime to extend worker wear time • Durable 10 gauge Hyperon® shell delivers breathability, comfort, and cut protection • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • PPG Tested • ANSI Level A5 Cut Resistance, ANSI Level 6 Abrasion Resistance and ANSI Level 4 Puncture Resistance	

APPLICATIONS	
Assembly, Appliance Manufacturing, Automotive, Maintenance, Material Handling, and Metal Handling	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD590B5	GPD590B6	GPD590B7	GPD590B8	GPD590B9	GPD590B10	GPD590B11	GPD590B12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	6
EN 388:2003 Puncture Resistance	6.4	4
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.		

Originator	Jennifer Walrich	Date	2/21/2017	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

