

Product Specifications

Style #GPD591



**Magid® Griffin Gear™ 13-Gauge Hyperon®
Polyurethane Palm Coated Work Gloves – Cut Level
A5**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® shell; polyurethane palm coating
Color(s)	Salt & pepper shell; grey palm coating
Size(s)	5-12
Cuff/Finish	Color-coded overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case
FEATURES & BENEFITS	
• 13-gauge steel-free Hyperon® shell delivers breathability, comfort, and 360° A5 cut protection • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Affordable protection to meet the needs of any safety program • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Machine washable for longer service life • ANSI Level A5 Cut Resistance, ANSI Level 6 Abrasion Resistance, and ANSI Level 4 Puncture Resistance	
APPLICATIONS	
Assembly, automotive manufacturing, appliance industry, metal stamping, metal fabrication, shipping and receiving, material handling and general maintenance	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Part Number	GPD5915	GPD5916	GPD5917	GPD5918	GPD5919	GPD59110	GPD59111	GPD59112
FUNCTIONAL PERFORMANCE								
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria								
Test Method					Clause	ANSI Level		
ASTM F2992 Cut Resistance					-	A5		
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)					-	6		
EN 388:2003 Puncture Resistance					6.4	4		
SERVICE LIFE								
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.								
Critical Defects		Holes/tears						
Major Defects		Dimensional or weight nonconformance, discoloration, other fabric defects						
LAUNDERING GUIDELINES								
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.								
GENERAL INFORMATION								
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.								

Originator	Scott Daigle	Date	8/21/2019	
Revised By	Scott Daigle	Date	12/18/2020	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.