

Product Specifications

Item #GPD612



D-ROC® **21G MAX**

**Magid® D-ROC® 21G MAX 21-Gauge
Polyurethane Palm Coated Work Gloves – Cut Level A6**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	21-gauge, seamless machine knit shell
Composition	21G fiber blend shell; polyurethane palm coating
Color(s)	Blue; gray
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), gray (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	PR
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• Ultra-thin 21-gauge knit construction delivers revolutionary bare-hand dexterity and tactile sensitivity • Specially engineered 21G lightweight fiber technology provides extreme comfort and A6 cut resistance • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Touchscreen compatible work gloves maintain user safety while operating electronic devices • Nitrile reinforced thumb saddle enhances durability at a critical wear point • Color-coded overcast acts as a visual aid for sizing and reduced fraying • Machine washable for longer service life • ANSI Level A6 Cut Resistance, ANSI Level 3 Abrasion Resistance, ANSI Level 2 Puncture Resistance	

APPLICATIONS	
Material handling, electrical contractors, assembly line, mechanics repair, maintenance and shipping & receiving. Especially relevant for jobs that require handling small parts and hand dexterity.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD6125	GPD6126	GPD6127	GPD6128	GPD6129	GPD61210	GPD61211	GPD61212

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A6
ASTM D338-10 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	3
EN 388:2003 Puncture Resistance	6.4	2

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Machine wash in warm water (not to exceed 104° F or 40° C) using mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Kim Schultz	Date	12/1/2025	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.