

Product Specifications

Style #GPD653W



D-ROC®

Magid® D-ROC® Hyperon® Winter Gloves with
VersaTek Grip® – Cut Level A6

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Fleece-lined, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® shell; VersaTek Grip® palm coating, fleece lining
Color(s)	Dark gray shell; black palm coating
Size(s)	6 – 12
Cuff/Finish	Color-coded elasticized overcast: gray (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 144 pairs per case, 12 pair minimum order increment

FEATURES & BENEFITS	
13-gauge Hyperon® shell delivers breathability, comfort, and cut protection - VersaTek Grip® Adaptive Coating Technology delivers unmatched durability while flexing with natural hand movements for precision handling of small parts - Insulcore® fleece liner defends against cold temperatures - Reinforced thumb saddle enhances durability at a critical wear point - Touchscreen compatible to maintain user safety while operating electronic devices - Color-coded overcast acts as a visual aid for sizing and reduces fraying - ANSI Level A6 Cut Resistance, ANSI Level 6 Abrasion Resistance, and ANSI Level 4 Puncture Resistance	

APPLICATIONS	
Construction, waste removal, transportation, and cold storage applications.	

AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Item Number	GPD653W6	GPD653W7	GPD653W8	GPD653W9	GPD653W10	GPD653W11	GPD653W12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A6
ASTM D3389 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	6
EN 388 Puncture Resistance	6.4	4
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. If it shows visible signs of wear, like tears, cuts, fraying seams or other structural integrity, replace immediately. Damaged PPE can compromise protection and increase risk of injury.		
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.		

Originator	Kim Schultz	Date	08/11/2026	
Revised By		Date		Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

