

Product Specifications

Item #GPD665



Magid® Griffin Gear™ Lightweight NitriX® Palm Coated Work Gloves with Reinforced Thumb Saddle – Cut Level A6

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit shell
Composition	Hyperon® shell; NitriX® palm coating; nitrile reinforced thumb saddle
Color(s)	Dark grey shell, black coating
Size(s)	5 – 11
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	Pair (12 pair minimum order)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• 13- gauge Hyperon® shell delivers cool comfort, excellent dexterity, and dependable cut protection • NitriX® Grip Technology palm coating delivers rock-solid grip in oily applications and increased wear life • Nitrile reinforced thumb saddle enhances durability at a critical wear point • Touchscreen compatible to maintain user safety while operating electronic devices • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Machine washable for longer service life • NEAT Tested • ANSI Cut Level A6 protection, ANSI Level 5 Abrasion Resistance and ANSI Level 5 Puncture Resistance	

APPLICATIONS							
Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling and Metal Stamping							
AVAILABLE STYLES							
Size	5	6	7	8	9	10	11
Item Number	GPD6655	GPD6656	GPD6657	GPD6658	GPD6659	GPD66510	GPD66511
FUNCTIONAL PERFORMANCE							
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria							
Test Method					Clause	ANSI Level	
ASTM F2992 Cut Resistance					-	A6	
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)					-	5	
EN 388:2003 Puncture Resistance					-	5	
SERVICE LIFE							
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.							
Critical Defects		Holes/tears					
Major Defects		Dimensional or weight nonconformance, discoloration, other fabric defects					
LAUNDERING GUIDELINES							
Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).							

Originator	Scott Daigle	Date	2/12/2020	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.