

Product Specifications

Style #GPD683



D-ROC®

Magid® D-ROC® AeroDex® 18-Gauge Extremely Lightweight VersaTek Grip™ Palm Coated Work Glove – Cut Level A6

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit
Composition	AeroDex® shell; VersaTek Grip™ palm coating
Color(s)	Blue shell; black palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 144 pairs per case, 12 pair minimum order increment

FEATURES & BENEFITS	
<ul style="list-style-type: none">• AeroDex® engineered yarn delivers extremely lightweight A6 cut resistance that is 50% lighter than a traditional HPPE of the same cut level• 18-gauge AeroDex shell delivers unmatched dexterity and tactile sensitivity making it agile enough for any job• AeroDex® is specially engineered to make your hands feel cooler than a comparable cut resistant glove• VersaTek™ Adaptive Coating Technology delivers unmatched durability while flexing with natural hand movements for precision handling of small parts• Intelligent VersaTek Grip adapts to amplify grip ability in wet, dry, or oily environments• Reinforced thumb saddle enhances durability at a critical wear point• Touchscreen compatible to maintain user safety while operating electronic devices• Color-coded overcast acts as a visual aid for sizing and reduces fraying• Machine washable for longer service life• ANSI Level A6 Cut Resistance, ANSI Level 6 Abrasion Resistance, and ANSI Level 3 Puncture Resistance	

APPLICATIONS

Appliance manufacturing, automotive, construction, glass handling, machining, metal handling, metal stamping, maintenance, assembly, and paper production.

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	GPD6835	GPD6836	GPD6837	GPD6838	GPD6839	GPD68310	GPD68311	GPD68312

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A6
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	6
ANSI/ISEA: 105-2011 Puncture Resistance	6.4	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	10/3/2022		
Revised By	Scott Daigle	Date	1/23/2023	Revision #	1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD