

# Product Specifications

Item #GPD700



**D-ROC®**  
by Magid

**Magid® D-ROC® Lightweight NitriX® Grip  
Technology Coated Work Glove - Cut Level A2**

| PRODUCT DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Product Classification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Special Purpose Work Glove – Cut Resistant, Coated                                                              |
| Construction/Design                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 13-gauge, seamless machine knit                                                                                 |
| Composition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Hyperon® fiber blended shell; NitriX® Grip Technology palm coating                                              |
| Color(s)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Salt & pepper shell; black palm coating                                                                         |
| Size(s)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 6 - 12                                                                                                          |
| Cuff/Finish                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Color-coded elasticized overcast: white (6), green (7), brown (8), yellow (9), black (10), grey (11), blue (12) |
| Unit of Measure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Pair (must be ordered in multiples of 12 pairs)                                                                 |
| Packaging                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 12 pairs per inner pack, 12 inner packs per case (144 pairs per case)                                           |
| FEATURES & BENEFITS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                 |
| <ul style="list-style-type: none"><li>• Durable 13 gauge Hyperon® shell delivers breathability, comfort, and cut protection</li><li>• NitriX® Grip Technology palm coating ensures a solid, secure grip in wet or dry applications</li><li>• Dark color hides dirt and grime to extend wear</li><li>• Color-coded overcast acts as a visual aid for sizing</li><li>• Elasticized finish on cuff reduces fraying</li><li>• Machine washable for longer service life</li><li>• PPG Tested</li><li>• ANSI Level A2 Cut Resistance under the ANSI/ISEA 105-2016 standard, ANSI Level 6 Abrasion Resistance and ANSI Level 4 Puncture Resistance</li><li>• Rated an ANSI Cut Level 2 under the ANSI/ISEA 105-2011 standard using the ASTM F-1790-97 test method</li></ul> |                                                                                                                 |
| APPLICATIONS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                 |
| Assembly, machining, automotive manufacturing, metal handling, maintenance and construction                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                 |

| AVAILABLE STYLES |         |         |         |         |          |          |          |
|------------------|---------|---------|---------|---------|----------|----------|----------|
| Size             | 6       | 7       | 8       | 9       | 10       | 11       | 12       |
| Part Number      | GPD7006 | GPD7007 | GPD7008 | GPD7009 | GPD70010 | GPD70011 | GPD70012 |

#### FUNCTIONAL PERFORMANCE

| US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria |        |            |
|---------------------------------------------------------------------------------------------------|--------|------------|
| Test Method                                                                                       | Clause | ANSI Level |
| Cut Resistance                                                                                    | -      | A2         |
| Abrasion Resistance                                                                               | -      | 6          |
| Puncture Resistance                                                                               | 6.4    | 4          |

#### European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

| Test Method          | Clause | EN Level |
|----------------------|--------|----------|
| Blade Cut Resistance | 6.2    | 3        |

#### SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| <b>Critical Defects</b> | Holes/tears                                                               |
| <b>Major Defects</b>    | Dimensional or weight nonconformance, discoloration, other fabric defects |

#### LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

#### GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

|                   |              |             |            |                     |
|-------------------|--------------|-------------|------------|---------------------|
| <b>Originator</b> | Efi Vrshek   | <b>Date</b> | 2/14/2013  |                     |
| <b>Revised By</b> | Dana Cornish | <b>Date</b> | 05/16/2022 | <b>Revision #</b> 4 |

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD